

Safety Data Sheet



1. **PRODUCT AND COMPANY INFORMATION**

Chemical Product Identification / Product Name:

ThermalBuck
EPS - Expanded Polystyrene
Synthetic Resin - Polyurea/Polyurethane Blend

Recommended Use and Restrictions: Insulation, flashing, and structural window attachment.

Manufacturer Information:

BRINC Building Products, Inc.
1270 Route 66
New Bethlehem, PA 16242
Telephone: 814 - 275 - 5002 (8am – 5pm EST weekdays)

2. **HAZARDS IDENTIFICATION**

Classification:

Eye effects: Category 2B
TOST: Single Exposure, category 3
Carcinogenicity: Category 2

Hazard Symbol:



Single Word:

Warning

Hazard Statement:

Heated foam may off-gas pentane which can accumulate at hazardous concentrations above the Lower Explosion Limit (LEL) if stored in closed containers or confined areas. No unusual conditions are expected from this product after it is aged several weeks. Sawing, sanding or machining plastic products can generate dust. Plastic dust may ignite or form explosive mixture with air in the presence of an ignition source. Product dust may be irritating to eyes, nose, skin, or respiratory system.

Precautionary Statements:

To prevent ignition, avoid smoking, keep from open flames and high temperatures. If heated above decomposition temperature or burned, product can emit an irritating dense black smoke and acid gases. Grinding, sawing or fabrication activities can produce dust particles which under certain conditions may ignite or form explosive dust atmospheres. Avoid creating any dust particulate in any area that is not well ventilated.

Appearance and Odor:

Polymeric coating over shaped foam core, various colors depending on brand, slight hydrocarbon odor.

Emergency Overview:

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>	<u>Degree of Hazard</u>
NFPA Rating:	2	2*	0	0 – Minimal (Insignificant)
HMIS Rating:	1	2*	0	1 – Slight (Minor)
				2 – Moderate
				3 – Serious (High)
				4 – Severe (Extreme)

Potential Health Effects Summary:

Dust particles may cause irritation or injury to the eyes. Contact with skin may cause irritation. Dust of this product may cause irritation of the nose, throat, or respiratory tract. Due to material form and application, ingestion is considered unlikely. May result in irritation of the digestive tract.

Routes of Entry: Inhalation, skin and eye contact, and ingestion.

Target Organs: Eyes, skin, gastrointestinal tract, and respiratory system.

Accuse Inhalation:

Breathing dust may cause temporary mechanical irritation and coughing. Overexposure to extremely high concentrations of pentane can cause narcotic effects. Signs and symptoms of overexposure to pentane include headache, nausea, dizziness, difficulty walking or sleepiness.

Chronic Inhalation: None identified.

Acute Skin Contact:

Direct contact with rough cut foam can cause mechanical abrasion to exposed skin.

Chronic Skin Contact: None identified.

Acute Eye Contact:

Eye contact may cause mild mechanical irritation, redness, tearing and blurred vision. Flush with large amounts of water for 15 minutes. Use fingers to ensure that the eyelids are separated and the eye is being irrigated. Get immediate medical attention.

Chronic Eye Contact: None identified.

Acute Ingestion:

Ingestion of this material is unlikely if used as intended. However, ingestion of this product may produce gastrointestinal irritation, nausea, and vomiting. Do not induce vomiting, unless directed to do so by medical personnel. Seek medical attention.

Chronic Ingestion: None identified.

Carcinogenicity:

EPS/Styrene monomer

ACGIH: A4 – Not classifiable as a Human Carcinogen

IARC: 2B – Possibly Carcinogenic to Humans (Vol. 60, 1994)

Medical Conditions Aggravated by Exposure:

Treat symptomatically. Specific data that address medical conditions that are generally recognized as being aggravated by exposure to this product are not available. However, chronic respiratory or eye conditions may worsen from exposure to these products.

3. COMPOSITION AND INGREDIENT INFORMATION

<u>Common Name</u>	<u>Chemical Name</u>	<u>CAS No.</u>	<u>Wt. %</u>
Polystyrene Foam	Ethenylbenzene homopolymer	9003-53-6	30-40%
Pentanes* (isomers)	n-pentane	09-66-0	≤ 1%
	Isopentane	78-78-4	
	Cyclopentane	287-92-3	
Styrene (residual)	Vinyl Benzene	100-42-5	0 – 0.1%
Synthetic Resin			60-70%

**This is a flammable blowing agent that off-gasses from product. Most of the pentane off-gasses prior to shipment. However, residual blowing agent may gradually off-gas from the foam during storage or use.*

4. FIRST AID MEASURES

Inhalation: Move person to fresh air. If irritation persists, seek medical attention.

Skin:

Wash with mild soap and running water. Remove and launder contaminated clothing before reuse. If irritation develops, seek medical attention.

Eyes: Flush eyes with running water min.15 minutes. Seek medical attention if irritation develops.

Ingestion:

Ingestion of this material is unlikely. If it does occur, do not induce vomiting; seek medical attention.

Fire: Move to fresh air. Administer oxygen and seek medical attention.

5. FIRE FIGHTING MEASURES

Flash Point and Method: Not applicable

Upper Flammable Limit (UFL): Not applicable

Lower Flammable Limit (LFL): Not applicable

Auto Ignition: EPS: 880° F (ASTM D-1929) for expanded polystyrene

Extinguishing Method:

Use water spray, water fog, fire-fighting foam or dry chemical or CO₂ extinguishing media.

Unusual Fire and Explosion Hazards:

Pentane vapors may be emitted from freshly expanded or processed foam or when product is heated. Hazardous concentrations may accumulate inside a sealed container or within confined space areas. Electrostatic discharge can be a source of ignition of accumulated pentane vapors exceeding the L.E.L (lower explosion limit) of 1.5% (15,000 ppm). If ignited, there may be a very high rate of flame propagation and/or an associated explosion. Assure proper ventilation of storage or shipping containers to prevent accumulation of hazardous concentrations of off-gassed pentane.

Hazardous Combustion Products:

Burning foam emits a dense, black, irritating smoke with acid gases. Primary combustion products are carbon monoxide, carbon dioxide, and styrene. Other undetermined hydrocarbon fraction could be released in small quantities.

6. ACCIDENTAL RELEASE MEASURES

Land Spill

Scoop up material and put into suitable container for recycling or disposal as a non-hazardous waste in an appropriate recycling or disposal facility. Remove all sources of flames, heating elements, gas engines, etc.

Water Spill

This material will float and disperse with wind and current. Contain the material with brooms, pick up or remove with a vacuum truck.

Air Release

This material will settle out of the air. If concentrated on land, it can then be scooped up for recycling or disposal as a non-hazardous waste.

7. HANDLING AND STORAGE

Storage Temperature: Below 170° F.

Storage Pressure: Not applicable.

General Storage:

Store in a well-ventilated area. Assure storage containers or areas and shipping containers are adequately ventilated. The flammable vapors of pentane (blowing agent) are heavier than air and may accumulate in low places. "No Smoking – No Matches – No Lighters – No Welding" rules should be enforced.

Appearance changes to color and sheen may occur within 3 month span of full UV exposure. No loss of physical properties should occur for 1 year or more.

8. EXPOSURE CONTROL / PERSONAL PROTECTION**Work Practices and Engineering Controls:**

Avoid unnecessary dust exposures when cutting or abrading by using adequate local exhaust or general ventilation. General dilution ventilation and/or local exhaust ventilation should be provided as necessary to maintain exposures below occupational exposure limits and to prevent accumulation of hazardous concentrations of off-gassed pentane (see section 5).

Personal Protective Equipment:

Eye: Safety glasses or goggles may be worn to reduce the risk of eye injury or irritation.

Respirators:

Respiratory protection is not normally required. If dusts are generated up to 10 times above occupational exposure limits, use a NIOSH-approved particulate respirator (disposable filtering dust mask type) with an efficiency rating of N95 or higher (e.g. 3M's 8210, Moldex 2300). Wear an air-purifying respirator with charcoal cartridges or a supplied air respirator when exposure to pentane exceeds exposure limits.

Skin: Gloves, long sleeved shirt and long pants may be worn, as needed, to prevent skin contact and irritation.

Other: None

<u>INGREDIENT</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>	<u>NIOSH REL</u>
Expanded Polystyrene			
PNOC:			
Inhalable	-	10 mg/m3	-
Respirable	5 mg/m3	3mg/m3	-
Total Particulate	15 mg/m3	-	-
Pentanes			
Pentane	1000 ppm	600 ppm	120 ppm 610 (Ceiling)
Cyclopentane	-	600 ppm	600ppm
Styrene	100 ppm 200 ppm (Ceiling) 600 ppm (5 minute peak)	20 ppm 40 ppm (STEL)	50 ppm 100 ppm (STEL)

Additional Information: The products listed in this SDS do not contain any form of Asbestos.

9. PHYSICAL AND CHEMICAL

Appearance: Pigmented	Flammability: Not flammable
Color: Orange or white with green coating	pH: Not available
Odor: Slight hydrocarbon odor	Flash Point: 700 F
Odor threshold: Not determined	Boiling Point: Not available
Physical State: Solid	Viscosity: Not applicable
Vapor Pressure (mm Hg @ 20 o C): 400 mm Hg	Freezing Point: Not available
Specific Gravity (Water=1): 1.05 to 1.18	Melting Point: Not available
Solubility in Water: Very slight	Decomposition temperature: 900 F
Evaporation rate: Not available	Relative Density: 0.5-4 pcf
Partition coefficient: N-octanol/water NA	Auto-ignition temperature: 750 F
Vapor Density (Air=1): Not applicable (Pentane blowing agent – 2.5) SYNTHETIC RESIN	

10. STABILITY and REACTIVITY

Stability: This is a stable material; avoid sources of ignition.

Reactivity: Refractive with oxidizing agents.

Incompatible Materials and Conditions to Avoid: Organic solvents, esters, amine and aldehydes will dissolve product.

Hazardous Decomposition Products: May decompose in a fire. See Section 5 of SDS for combustion products statement.

Hazardous Polymerization: Will not occur.

11. TOXICOLOGICAL INFORMATION

This product has not been tested as a separate entity. Therefore, the hazards must be evaluated on the basis of the individual ingredients, and those hazards must be assumed to be additive in the absence of complete information. The hazards described in this document have been evaluated on a threshold of 1.0% for all hazardous ingredients and 0.1% for all carcinogens.

Possible routes of exposure: See Section 2

Acute Effects: Acute health effects from this product are unlikely when used as intended.

Chronic Effects: Chronic health effects from this product are unlikely when used as intended.

Styrene Monomer

In March 1987, the International Agency for Research on Cancer (IARC) reclassified styrene as possibly carcinogenic to human (Group 2B) due to "inadequate evidence in humans", "limited evidence in animals" and "other relevant data". Previously, styrene was classified as a Group 3 compound (not classified as to carcinogenicity to humans). The IARC working group determined that the weight of data on genetic and related effects, together with the consideration that styrene metabolized in humans and animals to styrene oxide for which there is sufficient evidence of carcinogenicity in experimental animals and has been classified by IARC as probably carcinogenic to humans (Group 2A), was sufficient reason to recommend the change in classification.

Mutagenicity: Not available.

Reproductive effects: Not available.

Teratogenicity: Not available.

Synergistic materials: Not applicable

12. ECOLOGICAL INFORMATION

This material is not expected to cause harm to animals, plants or fish. Fish or animals may eat product and obstruct their digestive tract. It is not expected to harm ecosystems through its applied use.

13. WASTE DISPOSAL CONSIDERATIONS

RCRA Hazard Class: Non-hazardous

Waste Disposal:

Incinerate, recycle or dispose in a licensed facility. Do not discharge into waterways or sewer systems without proper authority. Any waste disposal must be in compliance with all federal, state and local laws and regulations. Chemical additions, processing or theories altering this material may make the waste management information presented in this SDS incomplete, inaccurate, or otherwise inappropriate. Waste characterization and disposal compliance are the responsibility solely of the party generating the waste or deciding to discard or dispose of the material. Do not allow any material to enter sewers, waterways, or contact the ground. Refer to RCRA 40 CFR 261, and/or any other appropriate federal, state or local requirements for proper classification information.

14. TRANSPORTATION INFORMATION

US DOT Information:

For domestic transportation purposes, this product is not regulated as a hazardous material by the US Department of Transportation (DOT) under Title 49 of the Code of Federal Regulations.

Canadian Transportation of Dangerous Goods (TDG) Requirements: Not regulated as dangerous goods.

15. REGULATORY INFORMATION

Clean Air Act

This product contains styrene, which is listed as a hazardous air pollutant

SARA Title III Regulations

This product contains pentane and residual styrene monomer, which OSHA defines as a hazardous chemical. This product may be portable under SARA sections 311 and 312, depending on the maximum on-site storage volumes. This product does not contain any substance(s) subject to the reporting requirements (i.e., at or above de minimis quantities) of sections 302 and 304 of Title III of the Superfund Amendments and Reauthorization Act (SARA-40 CFR 355). This product does not contain any substance(s) subject to reporting requirements (i.e., at or above de minimis quantities) of sections 302 and 304 of Title III of the Superfund Amendments and Reauthorization Act (SARA-40 CFR 372).

Toxic Substance Control Act (TSCA)

All ingredients are listed on the TSCA inventory.

California Proposition 65

This material contains detectable amounts of some chemicals known to the State of California to cause cancer. Styrene oxide is listed as known to the State of California to cause cancer. Styrene oxide is a metabolite of styrene monomer.

Component Analysis: State

The following components appear on one or more of the following state hazardous substance lists:

Component	CAS #	CA	MA	MI	MN	NJ	PA
Pentane (Isomers)	109-66-0 78-78-4 287-92-3	[?]	[?]		[?]	[?]	[?]
Styrene	100-42-5	[?]	[?]	[?]	[?]	[?]	[?]

Component Analysis: WHMIS IDL

The following components appear on one or more of the following state hazardous substance lists:

Component	CAS #	Minimum Concentration
Pentane (Isomers)	109-66-0 78-78-4 287-92-3	1% English Item 1243; French Item 1348
Styrene	100-42-5	0.1% English Item 1473; French Item 1508

WHMIS status: Exempt

Canadian regulations This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)
Canada	Domestic Substances List	Yes
Canada	Non Domestic Substances List	No
USA & Puerto Rico	Toxic Substance Control Act Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)/

16. ADDITIONAL INFORMATION:

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use.

updated November 2018